


































APLICACIONES PARA PISTON

PERFIL	REF.	PRESION	TEMPERATURA	VELOCIDAD	MATERIAL	DIAMETRO PISTON
		≤ (bar)	≤ (°C)	≤ (m/s)		
	DBM	300	- 40 + 130	0,50	NBR POLYESTER POM	25 ÷ 250
	D11W	500	- 40 + 130	0,50	NBR + TEJIDO POM	25 ÷ 300
	D11E	500	- 40 + 130	0,50	NBR + TEJIDO POM	—
	DPS DPC	350 700	- 40 + 130	0,50	NBR + TEJIDO POM	25 ÷ 50 30 ÷ 160
	DSM	700	- 40 + 130	0,50	NBR NBR + TEJIDO POM	45 ÷ 360
	EUD	400	- 40 + 110	0,50	POLIURETANO NBR POM	50 ÷ 160
	PHD	500	- 30 + 120	1,50	PTFE + BRONCE NBR POLIURETANO	50 ÷ 180
	DS	250	- 40 + 130	0,50	NBR NBR + TEJIDO	24 ÷ 200
	DS/NEO	700	- 40 + 130	0,50	NBR NBR + TEJIDO POM	24 ÷ 200
	MU/P	400	- 40 + 110	0,50	POLIURETANO	12 ÷ 202
	URS URFU	250	- 40 + 130	0,50	NBR + TEJIDO	14 ÷ 1000
	CH	400	- 40 + 130	0,50	NBR + TEJIDO POM	20 ÷ 545
	CH/GI	400	- 40 + 130	0,50	NBR + TEJIDO POM	—
	B/NWO+KR	500	- 40 + 130	0,50	NBR + TEJIDO POM	—

JUNTAS PARA PISTON

PERFIL	SERIE	PRESION	TEMPERATURA	VELOCIDAD	MATERIAL	APLICACION
		= (bar)	= (°C)	= (m/s)		
	UM U	120	- 30 + 130	0,25	NBR 90 Sh.	Neumática e hidráulica
	DE	80	- 30 + 130	0,25	NBR 75 Sh.	Neumática e hidráulica
	ISUN	400	- 30 + 110	0,50	Poliuretano PU	Hidráulica
	DS	250	- 40 + 130	0,50	NBR + Tela	Hidráulica
	DS/NEO	700	- 40 + 130	0,50	NBR + Tela + Apoyo	Hidráulica
	B	250	- 40 + 130	0,50	NBR + Tela	Hidráulica
	CH	400	- 40 + 130	0,50	NBR + Tela	Hidráulica
	DSM	700	- 40 + 130	0,50	NBR + Tela + Guía	Hidráulica Montaje abierto
	DBM	300	- 40 + 130	0,50	NBR + Poliéster + Guía	Hidráulica Montaje abierto
	D11W	500	- 40 + 130	0,50	NBR + Tela + Guía	Hidráulica Montaje abierto
	DPS	250	- 40 + 130	0,50	NBR + Tela + Guía	Hidráulica Montaje monobloc
	DPC	700	- 40 + 130	0,50	NBR + Tela + Guía	Hidráulica Montaje abierto

JUNTAS PARA VASTAGO

PERFIL	SERIE	PRESION	TEMPERATURA	VELOCIDAD	MATERIAL	APLICACION
		= (bar)	= (°C)	= (m/s)		
	UM U	120	- 30 + 130	0,25	NBR 90 Sh.	Neumática e hidráulica
	DI	120	- 30 + 130	0,25	NBR 90 Sh.	Neumática e hidráulica
	ISUN	400	- 40 + 110	0,50	Poliuretano PU	Hidráulica
	B	250	- 40 + 130	0,50	NBR + Tela	Hidráulica
	B/NEI	500	- 40 + 130	0,50	NBR + Tela + Apoyo	Hidráulica
	CH	400	- 40 + 130	0,50	NBR + Tela	Hidráulica
	SM	700	- 40 + 130	0,50	NBR + Tela + Apoyo	Hidráulica